





### Sleek, pocketable design

Transcend's M.2 SSD enclosure features a lightweight aluminum construction, making it both portable and durable while you are on the move. A LED indicator lets you know when the drive is in use.



# USB Type-A and Type-C supported

To accommodate devices with different USB ports, the M.2 SSD enclosure is engineered to convert to a USB Type-C port, offering flexibility of being used on different platforms with either USB Type-A or Type-C port.

\*Note: A USB Type-C to Type-A cable is included. Users will need to provide their own adapter or compatible cable to attach the M.2 SSD enclosure to USB Type-C devices.



### **Enhanced performance with UASP**

The M.2 SSD enclosure uses the USB 3.1 Gen 1 interface incorporated with UASP (USB Attached SCSI Protocol) that makes transfer speeds faster than with a sole USB 3.0 interface when used with a UASP-enabled host computer.





# Accessories M.2 SSD Enclosure Kit

## **Features**

- USB 3.1 Gen 1 interface with the support of UASP (USB Attached SCSI Protocol)
- SATA III 6Gb/s interface
- Lightweight yet durable aluminum construction
- USB Type-A and Type-C supported
- All-inclusive package

# **Specifications**

| A | op | ea | ra | n | се |
|---|----|----|----|---|----|
|---|----|----|----|---|----|

| Dimensions            | CM42: 81.41 mm x 33.6 mm x 7.5 mm (3.21" x 1.32" x 0.30")<br>CM80: 120.16 mm x 33.6 mm x 7.5 mm (4.73" x 1.32" x 0.30") |  |
|-----------------------|---|--|
| Weight                | CM42: 29 g (1.02 oz)<br>CM80: 41 g (1.45 oz)  |  |
| Interface             |   |  |
| Connection Interface  | USB 3.1 Gen 1   |  |
| Bus Interface         | SATA III 6Gb/s  |  |
| Operating Environment |   |  |
| Operating Temperature | 0°C (32°F) ~ 70°C (158°F)   |  |
| Storage Temperature   | -40°C (-40°F) ~ 85°C (185°F)  |  |
| Operating Voltage     | 5V  |  |
| Warranty              |   |  |
| Certificate           | CE / FCC / BSMI / KC / RCM  |  |
| Warranty              | Two-year Limited Warranty   |  |

**Ordering Information** 

Package

Package Contents

| 0MB | TS-CM42S |  |
|-----|----------|--|
|     | TS-CM80S |  |

Enclosure / M.2 adapter / Type-C to Type-A USB cable (45cm) / Metal plate / Aluminum sticker / Screwdriver / Mounting screws

Product specifications are subject to change without notice. Pictures shown may differ from actual products. Total accessible capacity varies depending on operating environment.